

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
<p>A header is required at the beginning of each XML file as follows: <?xml version="1.0" encoding="UTF-8" ?></p>							
<submission>	Opening tag for submission element Example with data: <submission type="PQRI-REGISTRY" version="5.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="Registry_Payment.xsd">						
	Type	Describes the setting for which data is being submitted	N/A	PQRI-REGISTRY	Character	20	Yes
	Version	The version of the file layout	N/A	5.0	Character	20	Yes
<file-audit-data> Sub-element of the submission element	Opening tag for file audit data	Note: This tag and the entire <file-audit-data> section are required in the XML document. This tag contains no data.					
<create-date> Sub-element of the file audit data element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <create-date>01-23-2012</create-date>						
	None	The month, day, and year the XML file was created.	N/A	MM-DD-YYYY (Must be a valid date)	Date	10	Yes
<create-time> Sub-element of the file audit data element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <create-time>23:01</create-time>						
	None	The hour and minutes representing the time the file was created.	N/A	HH:MM (Military format with or without colon)	Time	5	Yes
<create-by> Sub-element of the file audit data element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <create-by>RegistryA</create-by>						
	None	The entity who created the file.	N/A		Character	50	Yes

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
<version> Sub-element of the file audit data element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <version>1.0</version>						
	None	The version of the file being submitted.	N/A		Character	20	Yes
<file-number> Sub-element of the file audit data element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <file-number>1</file-number>						
	None	The number of the file.	N/A		Number	5	Yes
<number-of-files> Sub-element of the file audit data element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <number-of-files>1</number-of-files>						
	None	Total number of files.	N/A		Number	5	Yes
</file-audit-data>	Closing tag for file audit data	Note: This tag and the entire <file-audit-data> section are required in the XML document.					
<registry> Sub-element of the submission element	Opening tag for file registry data	Note: This tag is required in the XML document, however, it contains no data.					
<registry-name> Sub-element of the registry element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <registry-name>Model Registry</registry-name>						
	None	The registry name.	Registry Name	Registry Name	Character	100	Yes
<registry-id> Sub-element of the registry element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <registry-id>125789123</registry-id>						
	None	Used to identify the registry. Use Registry's Corporate TIN number.	Registry ID	Registry's 9 digit TAX Identification Number	Character	9	Yes

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
<p><submission-method> Sub-element of the file registry element</p>	<p>None</p>	<p>Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <submission-method>A</submission-method></p> <p>Submission Method: REGISTRY PQRS CODES: A = 12 months, 80%, 3 or more measures G = 12 months, 30 patients, measure group H = 12 months, 80%, min. of 15 patients, measure group I = 6 months, 80%, min. of 8 patients, measure group</p> <p>Note: Limit one xml file to a single submission method</p>	<p>Submission Method</p>	<p>A,G,H,I, (12 month reporting period = January 1, 2012 through December 31, 2012; 6 month reporting period = July 1, 2012 through December 31, 2012)</p>	<p>Character</p>	<p>1</p>	<p>Yes</p>
<p></registry></p>	<p>Closing tag for registry</p>	<p>Note: This tag is required in the XML document, however, it contains no data.</p>					

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
<p><measure-group> Sub-element of the submission element</p>		<p>Opening tag for measure group. There could be multiple measure groups in a single XML file. This element repeats if there are multiple measure groups.</p> <p>Example with data: <measure-group ID="C"></p>					
	ID	<p>ID of the measure group. A = Diabetes Mellitus C = CKD D = Preventive Care E = Perioperative Care F = Rheumatoid Arthritis G = Back Pain H = CABG I = Hepatitis C J = IVD K = CAP L = HF M = CAD N = HIV/AIDS O = Asthma P = COPD Q = IBD R = Sleep Apnea S = Cataracts T = Dementia U = Parkinsons Disease V = Hypertension W = Cardiovascular Prevention X = Not Applicable</p> <p>Note: If the submission-method is 'A' then the 'ID' attribute of measure-group should be 'X'</p>	N/A	A,C,D,E,F,G,H,I,J,K,L,M,N,O,P,Q,R,S,T,U,V,W,X	Character	1	Yes
<p><provider> Sub-element of the measure-group element</p>	Opening tag for provider	Note: This tag is required in the XML document, however, it contains no data. This element repeats if there are multiple providers					

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
<npi> Sub-element of the provider element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <npi>1257894658</npi>						
	None	National Provider Identifier as assigned by CMS.	National Provider Identifier (NPI)	10 digit National Provider Identifier	Character	10	Yes
<tin> Sub-element of the provider element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <tin>125789465</tin>						
	None	The tax identification number for individual NPI.	Tax Identification Number (TIN)	9 digit Tax Identification Number	Character	9	Yes
<email-address> Sub-element of the provider element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <email-address>johndoe@abc.com</email-address> Note: When the email-address value is null use <email-address xsi:nil="true"/> for this tag.						
	None	The email address of the provider's data submitted	Email Address		Character	100	Optional
<waiver-signed> Sub-element of the provider element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <waiver-signed>Y</waiver-signed>						
	None	Participation waiver signed? A participation waiver indicates the eligible professional has given the registry permission to submit data on their behalf.	Waiver Signed	Y,y	Character	1	Yes
<encounter-from-date> Sub-element of the provider element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <encounter-from-date>01-15-2012</encounter-from-date>						
	None	The month, day, and year of the first service encounter of the submission period ("From" date).	N/A	MM-DD-YYYY (Must be a valid date)	Date	10	Yes

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
<encounter-to-date> Sub-element of the provider element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <encounter-to-date>11-30-2012</encounter-to-date>						
	None	The month, day, and year of the last service encounter of the submission period ("To" date).	N/A	MM-DD-YYYY (Must be a valid date)	Date	10	Yes
<measure-group-stat> Sub-element of the provider data element	Opening tag for measure group stat	Note: If the measure-group 'ID' is 'X', do not include the <measure-group-stat> segment.					
<ffs-patient-count> Sub-element of the measure group stat element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <ffs-patient-count>2</ffs-patient-count>						
	None	Total number of Medicare Part B FFS patients seen for the PQRS measure group.	Patient count for the PQRS Measure Group		Number	10	Conditional; only required if measure-group 'ID' value is not 'X'
<group-reporting-rate-numerator> Sub-element of the measure group stat element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <group-reporting-rate-numerator>30</group-reporting-rate-numerator>						
	None	Number of instances of reporting for all applicable measures within the measure group, for each eligible instance (reporting rate numerator).	Number Eligible Instances Reported	Refer to PQRS Measure Group Specifications	Number	10	Conditional; only required if measure-group 'ID' value is not 'X'
<group-eligible-instances> Sub-element of the measure group stat element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <group-eligible-instances>30</group-eligible-instances>						
	None	Number of eligible instances (reporting denominator) for the PQRS measure group.	Eligible instances for the PQRS Measure Group	Refer to PQRS Measure Group Specifications	Number	10	Conditional; only required if measure-group 'ID' value is not 'X'
<group-reporting-rate> Sub-element of the measure group stat element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <group-reporting-rate>100.00</group-reporting-rate>						
	None	Percentage of reporting (Reporting Rate Numerator/Reporting Denominator).	Reporting Rate	0.00-100.00	Number	6	Conditional; only required if measure-group 'ID' value is not 'X'

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
</measure-group-stat>	Closing tag for measure group stat	Note: This tag is required in the XML document when the opening measure group stat tag is created.					
<pqri-measure> Sub-element of the provider data element	Opening tag for PQRI measure	Note: This tag is required in the XML document, however, it contains no data. This element repeats if there are multiple measures					
<pqri-measure-number> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Note: Only approved measures for the Registry will be accepted Example with data: <pqri-measure-number>119</pqri-measure-number>						
	None	The PQRS measure number.	PQRS Measure Number	Refer to PQRS Measure Specifications	Number	4	Yes
<collection-method> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <collection-method>B</collection-method>						
	None	Method Registry collected data from Eligible Professionals. B = Claims C = Practice Mgmt System D = Web Based Tool	Collection Method	B = Claims C = Practice Mgmt System D = Web Based Tool	Character	4	Yes
<eligible-instances> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <eligible-instances>100</eligible-instances>						
	None	Number of eligible instances (reporting denominator) for the PQRS measure.	Eligible instances for the individual PQRS Measure	Refer to PQRS Measure Specifications	Number	10	Yes
<meets-performance-instances> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <meets-performance-instances>70</meets-performance-instances>						
	None	Number of instances of quality service performed (performance numerator).	Number Instances of Quality Service Performed	Refer to PQRS Measure Specifications	Number	10	Yes

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
<performance-exclusion-instances> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <performance-exclusion-instances>20</performance-exclusion-instances>						
	None	Number of performance exclusions for the PQRS Measure	Performance Exclusions	Refer to PQRS Measure Specifications	Number	10	Yes
<performance-not-met-instances> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <performance-not-met-instances>10</performance-not-met-instances>						
	None	Number of instances which do not meet the performance criteria, even though reporting occurred.	Performance Not Met Instances	Refer to PQRS Measure Specifications	Number	10	Yes
<reporting-rate> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <reporting-rate>100.00</reporting-rate> Note: When the reporting-rate value is null use <reporting-rate xsi:nil="true"/> for this tag.						
	None	Percentage of reporting ((Performance Numerator + Performance Exclusions + Performance Not Met)/Reporting Denominator).	Reporting Rate	0.00-100.00	Number	6	Conditional; only required if measure-group is 'X' and reporting-rate is not a null value
<performance-rate> Sub-element of the PQRI measure element	Each element must have a closing tag that is the same as the opening tag but with a forward slash. Example with data: <performance-rate>88.00</performance-rate> Note: When the performance-rate value is null use <performance-rate xsi:nil="true"/> for this tag.						
	None	Percentage of performance (Performance Numerator/(Reporting Denominator-Performance Exclusions)).	Performance Rate	0.00-100.00	Number	6	Conditional; only required if performance-rate is not a null value
</pqri-measure>	Closing tag for pqri-measure	Note: This tag is required in the XML document, however, it contains no data.					
</provider>	Closing tag for provider	Note: This tag is required in the XML document, however, it contains no data.					

XML Element	Attributes	Description	Data Element	Valid Values	Data Type	Field Size	Data Required
</measure-group>	Closing tag for measure-group	Note: This tag is required in the XML document, however, it contains no data.					
</submission>	Closing tag for submission	Note: This tag is required in the XML document, however, it contains no data.					

Registry XML File Error Messages for Program Year 2012

01-01-2012 To 12-31-2012

Message Number	Data Element Name	XML Tag/Attribute	Condition	Message Status	Message Level	Message Description
1000	SYSTEM ERROR	SYSTEM ERROR	N/A	CRITICAL	Functional*	SYSTEM ERROR.
1001	GET XML FILE	GET XML FILE	Header text does not match XML Specifications	CRITICAL	Functional*	The system cannot find the file specified.
1002	GET XML FILE	GET XML FILE	Data Element Tag/Attribute mismatch	CRITICAL	Functional*	Invalid XML File.
1003	N/A	N/A	File is submitted after the submission deadline for the submission period	CRITICAL	Functional*	The submission deadline for the program initiative has passed. Files are no longer being accepted.
1004	File Number	<file-number>	File Number' element tag is incorrect	CRITICAL		File Number [<file-number>] tag is required.
1005	Number of Files	<number-of-files>	Number of Files' element tag is incorrect	CRITICAL		Number of Files [<number-of-files>] tag is required.
1006	Registry Name	<registry-name>	Registry Name element tag is incorrect	CRITICAL	Functional*	Registry Name [<registry-name>] tag is required.
1007	Registry ID	<registry-id>	Registry ID element tag is incorrect	CRITICAL	Functional*	Registry ID [<registry-id>] tag is required.
1014	Submission Method	<submission-method>	Submission Method element tag is incorrect	CRITICAL	Functional*	Submission Method [<submission-method>] tag is required.
1015	Submission Method	<submission-method>	Submission method is incorrect	CRITICAL	Functional*	Submission Method is not an allowable value.
1016	Submission Method	<submission-method>	Submission Method must be the same for all submissions	CRITICAL	Functional*	Submission Method has more than one method.
1017	Measure Group	<measure-group>	Measure Group element tag is incorrect	CRITICAL	Functional*	Measure Group [<measure-group ID>] tag is required.
1020	NPI	<npi>	NPI' element tag is incorrect	CRITICAL	Provider**	NPI [<npi>] tag is required.
1021	TIN	<tin>	TIN element tag is incorrect	CRITICAL	Provider**	TIN [<tin>] tag is required.
1022	Waiver Signed	<waiver-signed>	Waiver Signed element tag is incorrect	CRITICAL	Provider**	Waiver signed [<waiver-signed>] tag is required.
1023	Waiver Signed	<waiver-signed>	Waiver Signed can not be a value other than Y or y	CRITICAL	Provider**	Waiver must be signed to participate in the PQRI program initiative.
1024	PQRI Measure Number	<pqri-measure-number>	PQRI Measure Number element tag is incorrect	CRITICAL	Provider**	PQRI Measure Number [<pqri-measure-number>] tag is required.

* Functional level messages are relevant to the entire file.

** Provider level messages are specific to provider tin and/or npi's within the file.

Registry XML File Error Messages for Program Year 2012

01-01-2012 To 12-31-2012

Message Number	Data Element Name	XML Tag/Attribute	Condition	Message Status	Message Level	Message Description
1025	Eligible Instances	<eligible-instances>	Eligible Instances element tag is incorrect	CRITICAL	Provider**	Eligible Instances [<eligible-instances>] tag is required.
1026	Eligible Instances	<eligible-instances>	Eligible Instances is not a valid value	CRITICAL	Provider**	Eligible Instances is not an allowable value.
1027	Meets Performance Instances	<meets-performance-instances>	Meets Performance Instances' element tag is incorrect	CRITICAL	Provider**	Meets Performance Instances [<meets-performance-instances>] tag is required.
1028	Meets Performance Instances	<meets-performance-instances>	Meets Performance Instances is not a valid value	CRITICAL	Provider**	Meets Performance Instances is not an allowable value.
1029	Performance Exclusion Instances	<performance-exclusion-instances>	Performance Exclusion Instances element tag is incorrect	CRITICAL	Provider**	Performance Exclusion Instances [<performance-exclusion-instances>] tag is required.
1030	Performance Not Met Instances	<performance-not-met-instances>	Performance Not Met Instances element tag is incorrect	CRITICAL	Provider**	Performance Not Met Instances [<performance-not-met-instances>] tag is required.
1031	Reporting Rate	<reporting-rate>	Reporting Rate element tag is incorrect	CRITICAL	Provider**	Reporting Rate [<reporting-rate>] tag is required.
1032	Performance Rate	<performance-rate>	Performance Rate element tag is incorrect	CRITICAL	Provider**	Performance Rate [<performance-rate>] tag is required.
1034	Submission	<submission>	Submission Type element tag is incorrect	CRITICAL	Functional*	Submission "Type" attribute is required.
1035	Submission	type	Submission Type is not equal to 'PQRI-REGISTRY'	CRITICAL	Functional*	Submission Type is not an allowable value.
1038	Submission	<submission>	Submission Version attribute is incorrect	CRITICAL	Functional*	Submission "Version" attribute is required.
1042	File Number	<file-number>	Invalid data: null, space, invalid type and length	CRITICAL	Functional*	File Number is not an allowable value.
1043	Number of Files	<number-of-files>	Invalid data: null, space, invalid type and length	CRITICAL	Functional*	Number of Files is not an allowable value.
1044	Registry Name	<registry-name>	Invalid data: null, space, invalid type and length	CRITICAL	Functional*	Registry Name is not an allowable value.
1045	Registry ID	<registry-id>	Invalid data: null, space, invalid type and length	CRITICAL	Functional*	Registry ID is not an allowable value.
1049	Measure Group	<measure-group>	Invalid data: null, space, invalid type and length	CRITICAL	Functional*	Measure Group ID is not an allowable value.

* Functional level messages are relevant to the entire file.

** Provider level messages are specific to provider tin and/or npi's within the file.

Registry XML File Error Messages for Program Year 2012

01-01-2012 To 12-31-2012

Message Number	Data Element Name	XML Tag/Attribute	Condition	Message Status	Message Level	Message Description
1050	Provider NPI	<npi>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Provider NPI is not an allowable value.
1051	Provider TIN	<tin>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Provider TIN is not an allowable value.
1053	PQRI Measure Number	<pqri-measure-number>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	PQRI Measure Number is not an allowable value.
1058	Performance Exclusion Instances	<performance-exclusion-instances>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Performance Exclusion Instances is not an allowable value.
1059	Performance Not Met Instances	<performance-not-met-instances>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Performance Not Met Instances is not an allowable value.
1060	Reporting Rate	<reporting-rate>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Reporting Rate is not an allowable value.
1063	Performance Rate	<performance-rate>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Performance Rate is not an allowable value.
1065	Create Date	<create-date>	Invalid date format	CRITICAL	Functional*	Create Date is not an allowable value.
1067	Create Time	<create-time>	Invalid time format	CRITICAL	Functional*	Create Time is not an allowable value.
1068	Create By	<create-by>	Invalid data	CRITICAL	Functional*	Create By is not an allowable value.
1069	Create Date	<create-date>	Create Date element tag is incorrect	CRITICAL	Functional*	Create Date [<create-date>] tag is required.
1070	Create Time	<create-time>	Create Time element tag is incorrect	CRITICAL	Functional*	Create Time [<create-time>] tag is required.
1071	Create By	<create-by>	Create By element tag is incorrect	CRITICAL	Functional*	Create By [<create-by>] tag is required.
1075	Encounter From Date	<encounter-from-date>	Encounter From Date element tag is incorrect	CRITICAL	Provider**	Encounter From Date [<encounter-from-date>] tag is required.

* Functional level messages are relevant to the entire file.

** Provider level messages are specific to provider tin and/or npi's within the file.

Message Number	Data Element Name	XML Tag/Attribute	Condition	Message Status	Message Level	Message Description
1076	Encounter From Date	<encounter-from-date>	1) Encounter From Date is not in a valid format - Valid Format = MM-DD-YYYY - Month cannot be 00 and cannot be greater than 12. - Date cannot be 00 and cannot be greater than 31. - Date cannot exceed limit for month OR 2) Encounter From Date is all 9's	CRITICAL	Provider**	Encounter From Date [encounter-from-date] is not an allowable value.
1077	Encounter From Date	<encounter-from-date>	Encounter From Date can not be greater than Encounter To Date	CRITICAL	Provider**	Encounter From Date [encounter-from-date] can not be greater than Encounter To Date.
1078	Encounter To Date	<encounter-to-date>	Encounter To Date element tag is incorrect	CRITICAL	Provider**	Encounter To Date [encounter-to-date] tag is required.
1079	Encounter To Date	<encounter-to-date>	1) Encounter To Date is not in a valid format - Valid Format = MM-DD-YYYY - Month cannot be 00 and cannot be greater than 12. - Date cannot be 00 and cannot be greater than 31. - Date cannot exceed limit for month OR 2) Encounter To Date is all 9's	CRITICAL	Provider**	Encounter To Date [encounter-to-date] is not an allowable value.
1080	FFS Patient Count	<ffs-patient-count>	FFS Patient Count element tag is incorrect	CRITICAL	Provider**	FFS Patient Count [ffs-patient-count] tag is required.
1081	FFS Patient Count	<ffs-patient-count>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	FFS Patient Count is not an allowable value.
1082	Group Reporting Rate Numerator	<group-reporting-rate-numerator>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Group Reporting Rate Numerator is not an allowable value.

* Functional level messages are relevant to the entire file.

** Provider level messages are specific to provider tin and/or npi's within the file.

Registry XML File Error Messages for Program Year 2012

01-01-2012 To 12-31-2012

Message Number	Data Element Name	XML Tag/Attribute	Condition	Message Status	Message Level	Message Description
1083	Group Reporting Rate Numerator	<group-reporting-rate-numerator>	Group Reporting Rate Numerator element tag is incorrect	CRITICAL	Provider**	Group Reporting Rate Numerator [<group-reporting-rate-numerator>] tag is required.
1084	Group Eligible Instances	<group-eligible-instances>	Group Eligible Instances element tag is incorrect	CRITICAL	Provider**	Group Eligible Instances [<group-eligible-instances>] element tag is required.
1085	Group Eligible Instances	<group-eligible-instances>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Group Eligible Instances is not an allowable value.
1086	Group Reporting Rate	<group-reporting-rate>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Group Reporting Rate is not an allowable value.
1087	Group Reporting Rate	<group-reporting-rate>	Group Reporting Rate element tag is incorrect	CRITICAL	Provider**	Group Reporting Rate [<group-reporting-rate>] element tag is required.
1089	Measure Group Stat	<measure-group-stat>	Measure Group Stat element can not be blank when Measure Group ID does not equal X	CRITICAL	Functional*	Measure Group Stat [<measure-group-stat>] element is required when Measure Group ID does not equal X.
1090	Measure Group Stat	<measure-group-stat>	Measure Group Stat tag is invalid	CRITICAL	Provider**	Provider has more than one Measure Group Stat.
1091	Version	<version>	Version element tag is incorrect	CRITICAL	Functional*	Version [<version>] tag is required.
1092	Version	<version>	Invalid version format	CRITICAL	Functional*	Version [<version>] is not an allowable value.
1093	Encounter From Date	<encounter-from-date>	Encounter From Date is not within the Reporting Period range.	CRITICAL	Provider**	Encounter From Date [<encounter-from-date>] is not within the Reporting Period range.
1094	Encounter To Date	<encounter-to-date>	Encounter To Date is not within the Reporting Period range.	CRITICAL	Provider**	Encounter To Date [<encounter-to-date>] is not within the Reporting Period range.
1095	Measure Group Stat	<measure-group-stat>	Measure Group Stat element tag is incorrect	CRITICAL	Provider**	PQRI Measure [<pqri-measure>] or Measure Group Stat [<measure-group-stat>] element tag is required.
1096	Measure Group Stat	<measure-group-stat>	Measure Group Stat element tag is not valid with Measure Group ID	CRITICAL	Provider**	Measure Group Stat [<measure-group-stat>] element is not valid with the Measure Group ID.

* Functional level messages are relevant to the entire file.

** Provider level messages are specific to provider tin and/or npi's within the file.

Registry XML File Error Messages for Program Year 2012

01-01-2012 To 12-31-2012

Message Number	Data Element Name	XML Tag/Attribute	Condition	Message Status	Message Level	Message Description
1097	Provider	<provider>	Provider element tag is incorrect	CRITICAL	Provider**	Provider [<provider>] element tag is required.
1099	File Audit Data	<file-audit-data>	File Audit Data element tag is incorrect	CRITICAL	Functional*	File Audit Data [<file-audit-data>] element tag is required.
1100	Registry	<registry>	Registry element tag is incorrect	CRITICAL	Functional*	Registry [<registry>] element tag is required.
1101	PQRI Measure	<pqri-measure>	PQRI Measure element tag is incorrect	CRITICAL	Functional*	PQRI Measure [<pqri-measure>] element tag is required.
1102	Collection Method	<collection-method>	Collection Method element tag is incorrect	CRITICAL	Provider*	Collection Method [<collection-method>] element tag is required.
1103	Collection Method	<collection-method>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Collection Method is not an allowable value.
1107	Email Address	<email-address>	Email Address element tag is incorrect	CRITICAL	Provider*	Email Address [<email-address>] element tag is required.
1108	Email Address	<email-address>	Invalid data: null, space, invalid type and length	CRITICAL	Provider**	Email Address is not an allowable value.
1109	Eligible Instances	<eligible-instances>	Eligible Instances is less than Meets Performance Instances	CRITICAL	Provider**	Eligible Instances can not be less than Meets Performance Instances.
1111	Reporting Rate	<reporting-rate>	Measure Group is X and Reporting Rate is Null	CRITICAL	Provider**	Reporting Rate is required when the Measure Group is X.
1112	Measure Group	<measure-group>	Measure Group ID equals X and submission method does not equal A	CRITICAL	Functional*	Measure Group ID is not valid for Submission Method.
1113	Submission	version	Submission Version is not equal to '5.0'	CRITICAL	Functional*	Submission Version is not an allowable value.
1114	PQRI Measure Number	<pqri-measure-number>	PQRI measure number is not a valid measure in accordance with the 2012 PQRS Qualified Registries Quality Measures Crosswalk	CRITICAL	Provider**	PQRI measure number is not a valid measure in accordance with the 2012 PQRS Qualified Registries Quality Measures Crosswalk.

* Functional level messages are relevant to the entire file.

** Provider level messages are specific to provider tin and/or npi's within the file.

Message Number	Data Element Name	XML Tag/Attribute	Condition	Message Status	Message Level	Message Description
1115	Registry ID	<registry-id>	Registry ID is not eligible to submit for the 2012 measures in accordance with the 2012 PQRS Qualified Registries Quality Measures Crosswalk.	CRITICAL	Functional*	Registry ID is not eligible to submit for the 2012 measures in accordance with the 2012 PQRS Qualified Registries Quality Measures Crosswalk.
1116			TIN/NPI combination not found.		Warning	TIN/NPI combination provided was checked against previous TIN/NPI participants. Verify if this is a new provider or if the TIN/NPI listed is accurate.

* Functional level messages are relevant to the entire file.

** Provider level messages are specific to provider tin and/or npi's within the file.